

# Challenge Series

## Satellite High Speed DVB-S2 IP Modem

### SK-IP / SK-DV



#### CCM, VCM, ACM Functionality

The satellite high speed DVB-S2 IP modem SK-IP provides a platform for transferring IP/Ethernet data over DVB-S2 satellite connections. Ethernet frames and IP packets are encapsulated directly within DVB-S2 baseband frames, which results in low encapsulation overhead.

#### OptiACM

An integrated OptiACM controller provides adaptive or variable FEC- and modulation setting for point-to-point or point-to-multipoint IP applications.

#### DaVid Technology

Utilizing DaVid technology, WORK Microwave's DVB-S2 Modem SK-DV system offers simultaneous transportation of IP data (network connection) and live broadcasting (video content) over a single satellite carrier. The DaVid technology works by aggregating Multiple Transport Streams and IP data into a DVB-S2 multiplex and provides a powerful system for end-user control of all transmission types.

#### VideoACM

An integrated VideoACM controller provides adaptive or variable FEC- and modulation setting for point-to-point or point-to-multipoint Transport Stream transmissions.

The modulator provides the modulated signal from 50 to 180 MHz IF or at L-band. With the L-band output also a 10 MHz reference signal for a block-upconverter can be enabled on the TX port, as well as DC power 24 V or 48 V (Option DC24 or DC48).

The demodulator accepts an L-Band signal in the range from 950 to 2150 MHz on two inputs or alternatively an IF signal in the range from 50 to 180 MHz on a single input. On L-Band devices LNBS can be powered directly over the inputs.

#### High signal integrity

Low spurious emissions allow using the modem also in environments with demanding requirements, like high power video uplinks. Sophisticated temperature compensation guarantees output stability over a very wide temperature range.

#### Operating and control - easy integration into your system

The modem can be operated via the push buttons on the front panel using self-explanatory display menus or via remote control (RS232, RS422/485 and TCP/IP over Ethernet). For the remote control either addressable packet based commands, a WEB interface (HTTP web browser interface) or SNMP can be used. Detailed monitoring of system parameters is possible.

## Key features

- DVB-S2 satellite modem for IP/Ethernet data (SK-IP / SK-DV) and Transport Stream (SK-DV) transmission.
- DVB-S2 compliant (ETSI EN 302 307)
- QPSK / 8PSK / 16APSK / 32APSK modulation
- Normal and short FEC frames, pilots on or off
- Physical layer framing (PL scrambling with codes 0 to 262141) according to DVB-S2 standard
- Symbol rates from 60 ksps to 60 Msps
- Roll-Off: 35%, 25%, 20%
- Roll-Off 15%, 10%, 5% with Firmware Option ...S
- Adjustable digital slope equalizer
- Low spurious output
- OptiACM system for optimized bandwidth usage and extended weather insensitivity for IP transmission
- Gigabit Ethernet data interface
- IP and Baseband traffic shaping
- Generic Stream Encapsulation (GSE) direct to DVB-S2 base band frames
- Operates as Layer 2 Bridge, Layer 3 Bridge or Layer 3 Router
- 2 ASI Input and 2 ASI Output Interfaces (SK-DV)
- Transport Stream Input for DVB-S2 Multiple Input Stream operation, capacity calculator, optional capacity limitation per TS input (SK-DV only)
- Transport Stream over IP Inputs (Option T11,T12) (SK-DV only)
- Support of 2 Multiple Transport Stream Inputs and Outputs (Option MT2) (SK-DV))
- VideoACM system for optimized bandwidth usage and extended weather insensitivity for Transport Stream video transmission
- BISS-E encryption of transport streams on transmit side (Option BI), supports multi program transport stream.
- Transmit mute input
- Tx Monitor Output on Frontpanel
- Remote control through RS232, RS422/485 (2-wire or 4-wire) interfaces, TCP/IP over Ethernet, Web browser interface, SNMP (MIBs are provided)
- 10 MHz Reference OCXO included
- Summary alarm output (dual change over switch contacts)
- Operating temperature range 0°C to 50°C (32°F to 122°F)
- CE compliant
- **3 years warranty**

## Customer Field selectable Firmware Option

Different maximum requirements are supported on the modulator, depending on the selected firmware option. The firmware option is password upgradeable in the field, which allows easy enhancement of the modulators if requirements change. A table with the available firmware options is located at the end of this datasheet.

## Open questions, demo units

If you need more information about WORK Microwave's satellite modems or if you would like to have demo a unit, please contact us via e-mail: [info@drawcom.com.au](mailto:info@drawcom.com.au) or call us. We are glad to assist you.

# Challenge Series

## Satellite High Speed DVB-S2 IP Modem

### SK-IP / SK-DV

Modulator Part of Modem Type:	SK-IP / SK-DV	
<b>Signal Outputs:</b>	SK-xx-Lx-xx: 1x L-Band output (950..2150 MHz) SK-xx-Vx/Lx-xx: 1x L-Band output (950..2150 MHz) 1x VHF-Band output (50..180 MHz)	
	VHF Band Output	L-Band Output
<b>IF-Output Frequency:</b>	50 ... 180 MHz	950 ... 2150 MHz
<b>Frequency Resolution:</b>	1 Hz	1 Hz
<b>Phase Noise:</b>		
10 Hz	-70	-65
100 Hz	-80	-75
1 kHz	-88	-88
10 kHz	-90	-90
100 kHz	-100	-100
1 MHz	-115	-115
	max. values in dBc/Hz	
<b>IF-Output Characteristics:</b>	Impedance: 50 Ω or 75 Ω Return Loss: >18 dB Output Power: -25 dBm ... 5 dBm, 0.1 dB steps, ±0.5 dBm accuracy Output Power muted: <-85 dBm Connector: BNC female	Impedance: 50 Ω or 75 Ω Return Loss: >18 dB Output Power: -30 dBm ... 0 dBm, 0.1 dB steps, ±0.5 dBm accuracy Output Power muted: <-85 dBm Connector: N female (50 Ω) F female (75 Ω) 10 MHz reference output on L-Band output: 1.5 ±1.5 dBm (can be switched on/off) DC output on L-Band output: 24 V or 48 V, 4 A max (can be switched on/off) (option DC24 or DC48)
<b>Monitoring Output (on front panel):</b>	Output Power: -20 dB of IF Output Impedance: 50 Ω Return Loss: >20 dB Connector: SMA female	Output Power: -20 dB of L-Band Output Impedance: 50 Ω Return Loss: >20 dB Connector: SMA female
<b>Spurious Outputs:</b>	Signal related: <-70 dBc, unmodulated carrier, 50 ... 90 MHz or 100 ... 180 MHz <-45 dBc, unmodulated carrier, out of band	Signal related: <-70 dBc, unmodulated carrier, 950 ... 1900 MHz <-55 dBc, unmodulated carrier, 1900 ... 2150 MHz <-45 dBc, unmodulated carrier, out of band
<b>Frequency and Clock Stability</b>	±2 x 10 <sup>-8</sup> (-30°C ... 60°C, after warm up), aging: ±1 x 10 <sup>-9</sup> per day, ±1 x 10 <sup>-7</sup> per year	
<b>Symbol Rate:</b>	Max. Range: 60 ksps ... 60 Msps (depending on firmware option) Step size: 1 sps	
<b>Modulation / Coding DVB-S2:</b>	Outer BCH Code: FEC-Frames nldpc = 64800 (normal FEC Frame) nldpc = 16200 (short FEC Frame) Inner LDPC Code: QPSK 1/4, 1/3, 2/5, 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 8PSK 3/5, 2/3, 3/4, 5/6, 8/9, 9/10 16APSK 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 32APSK 3/4, 4/5, 5/6, 8/9, 9/10 Physical Layer Framing: yes Physical Layer Signaling: yes Pilots Insertion: on / off Physical Layer Scrambling: N = 0 ... 262141 all according ETSI EN 302307	
<b>Signal Spectrum Mask:</b>	α = 0.35, 0.25, 0.20 according ETSI EN 302307 α = 0.15, 0.10, 0.05 (with Firmware Option ... S, other values on request)	
<b>Transport Stream Inputs:</b>	2x ASI (BNC female 75 Ω) (SK-DV only) Supporting 1 Multiple Transport Stream Input (auto switching dual input) With option MT2: 2x ASI (BNC female 75 Ω) (SK-DV only) Supporting 2 Multiple Transport Stream Inputs or 1 Multiple Transport Stream (auto switching dual input) Additionally with option T11 or T12 up to two individual Transport Stream over IP Inputs (Connector RJ-45, 100/1000 Mbps, auto sensing), IPv4, UDP and RTP support, FEC according SMPTE 2022 1/2, Jitter tolerance 1... 500 ms, Conversion TS over IP to TS.	
<b>Multiple Transport Stream Input Operation:</b>	Individual modulation and FEC (MODCOD) configuration per TS input, capacity calculator, capacity limitation per TS input can be activated. Input stream synchronization and Null-Packet deletion according to ETSI EN 302307, Annex D.2, D.3. (SK-DV only)	
<b>Transport Stream Frames Size:</b>	188 or 204 bytes	
<b>Still Picture Playout:</b>	As standard a color bar pattern is transmitted with main profile at main level (MPML) MPEG-2 encoding, 4:3 aspect ratio, 25 Hz frame rate, interlaced (suitable for PAL or SECAM). As option an alternative, customized still picture can be loaded (different content, different aspect ratio, different frame rate).	

Specifications continued next page

# Challenge Series

## Satellite High Speed DVB-S2 IP Modem

### SK-IP / SK-DV

Specifications continued:

Demodulator Part of Modem Type:	SK-IP / SK-DV	
<b>Signal Inputs:</b>	SK-xx-xx-L75: 2x L-Band input (950..2150 MHz) SK-xx-xx-Vx/L75: 1x L-Band input (950..2150 MHz) 1x VHF-Band input (50..180 MHz)	
	<b>VHF Band Input</b>	<b>L-Band Inputs</b>
<b>IF-Input Frequency:</b>	50 ... 180 MHz	950 ... 2150 MHz
<b>IF-Input Characteristics:</b>	Impedance: 50 $\Omega$ or 75 $\Omega$ Return Loss: >18 dB Input Power: -60 dBm -15 dBm (total aggregate power) IF-Connector: BNC female	Impedance: 75 $\Omega$ Return Loss: >13 dB Input Power: -70 dBm ... -20 dBm (total aggregate power) IF-Connector: 2x F female, input selectable LNB DC-Feed: 13.5V or 18 VA (450mA) switchable, 22 kHz tone on/off, short circuit protected
<b>Symbol Rate:</b>	Max. Range: 60 ksps ... 60 Msps (QPSK, 8PSK) 60 ksps ... 45 Msps (16APSK) 60 ksps ... 40 Msps (32APSK) Step size: 1 sps	
<b>Demodulation / Decoding DVB-S2:</b>	Outer BCH Code: FEC-Frames Inner LDPC Code: QPSK 1/4, 1/3, 2/5, 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 8PSK 3/5, 2/3, 3/4, 5/6, 8/9, 9/10 16APSK 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 32APSK 3/4, 4/5, 5/6, 8/9, 9/10 Demodulator auto detection: Modulation- and FEC-type, pilots on/off are automatically detected Physical Layer Scrambling: N = 0 ... 262141 all according ETSI EN 302307	nldpc = 64800 (normal FEC Frame) nldpc = 16200 (short FEC Frame)
<b>Signal Spectrum Mask:</b>	$\alpha$ = 0.35, 0.25, 0.20 according ETSI EN 302307 $\alpha$ = 0.15, 0.10, 0.05 (compatible)	
<b>Transport Stream Output:</b>	2x ASI (BNC female 75 $\Omega$ ) (SK-DV only) Supporting Single Transport Stream Operation or 1 Multiple Transport Stream Operation (Dual Output) 1x RTP/UDP IP over Ethernet according to IETF RFC 2250 With Option MT2 (SK-DV only): Processing of 2 Multiple Transport Streams Support of Null Packet Reinsertion according to ETSI EN 302 307 Annex G.3 2x ASI (BNC female 75 $\Omega$ ), can be assigned arbitrarily Up to 2x RTP/UDP IP over Ethernet according to IETF RFC 2250	
<b>Transport Stream Frame Size:</b>	188 bytes (SK-DV only)	

Specifications continued next page

# Challenge Series

## Satellite High Speed DVB-S2 IP Modem

### SK-IP / SK-DV

Specifications continued:

Common Parameters:	SK-IP / SK-DV
<b>Baseband Channels:</b>	16 baseband channel with separate DVB-S2 baseband settings (MODCOD, FEC frame length, pilots, encapsulation type, multistream ID, timeout)
<b>OptiACM:</b>	CCM / VCM / ACM functionality for point-to-point and point-to-multipoint links 16 ACM channels with separate MODCOD range and Es/N0 sensitivity ACM channels arbitrary assignable to baseband channels
<b>BB Traffic Shaper:</b>	Baseband channel limits based on symbol rate for virtual share of the carrier Guaranteed and limited bandwidth individually configurable
<b>Data Interface:</b>	Ethernet (1xRJ-45, 10/100/1000 Mbps auto sensing)
<b>Data Rate:</b>	up to 178 Mbps or 80000 pps
<b>Network Operation:</b>	Layer 2: Bridge (Ethernet frame transmission) STP/RSTP Layer 3: Bridge/Router (IP packet transmission), IPv4, IPv6 256 IP/subnet routes per port 16 DVB-S2 baseband channels
<b>Data Encapsulation:</b>	Generic Stream Encapsulation (GSE) according TS 102606
<b>IP Traffic Shaper:</b>	64 independent rules Guaranteed and limited bandwidths Fixed or dynamically integrated into ACM (bind to MODCOD) Match criteria: source/destination IP subnet, source MAC, UDP/TCP port ranges, TOS/DS field, packet size (Active IP Traffic shaper reduces max. packet rate to typ. 50000 pps)
<b>Transport Stream Security (Option BI):</b>	BISS-E Scrambler on transmit side, compliant to EBU Tech 3292 rev. 2 (SK-DV only) For use with unit supporting 1 Multiple Transport Stream input. Supports Single or Multi Program Streams in BISS Mode 0, 1 and E BISS Mode 0: no scrambling, MPEG transport stream is transferred untouched BISS Mode 1: MPEG transport stream is scrambled using 12-hexadecimal-character Clear Session Word BISS Mode E: MPEG transport stream is scrambled using a session word which is derived from a 16-hexadecimal-character Encrypted Session Word and 14-hexadecimal-character Injected Identifier  Max. input rate for Clear Session Word and Encrypted Session Word: - 10 times per 5 minutes - 1 time per 10 seconds
<b>Monitoring and Control Interface:</b>	Protocol: SNMP Connection: UDP over Ethernet (10/100 Mbps auto sensing) IPv4, IPv6, connector RJ-45 Protocol: HTTP (web browser interface) Connection: TCP/IP over Ethernet (10/100 Mbps, auto sensing) IPv4, IPv6, connector RJ-45 Protocol: Multipoint Connection: RS232 or RS422/RS485 (configurable), connector DSUB09 female or TCP/IP over Ethernet (10/100 Mbps, auto sensing) IPv4, IPv6, connector RJ-45
<b>Alarm Interface: Mute Input:</b>	Alarm: two potential free contacts (DPDT), Mute Input: TTL logic input with internal pull up Connector DSUB09
<b>Internal Fan</b>	FAN included
<b>Temperature Range:</b>	0°C ... 50°C operating -30°C ... 80°C storage
<b>Relative Humidity:</b>	<95% non condensing
<b>User Interface:</b>	LCD-Display 2 x 40 characters, 4 cursor keys, 4 function keys
<b>Mains Power Input:</b>	100 ... 240 V AC nominal, 90...264 V AC max, 50...60 Hz
<b>Mains Power Consumption:</b>	Typ: 65 VA / 45 W, Max 190 W (with option DC24, DC power on) Max 300 W (with option DC48, DC power on)
<b>Mains Power Input Connector:</b>	IEC C14
<b>Mains Fuse:</b>	2 x 3.15 A time-lag fuse (standard) 2 x 5 A time lag fuse (with option DC24 or DC48)
<b>Dimension and Weight:</b>	483 x 44 x 470 mm <sup>3</sup> (WxHxD), 1 RU (19") approx. 8 kg (standard) approx. 10 kg (with option DC24 or DC48)

Specifications are subject to change

**Order**

**Information:** SK-[Device Type]-[Output Band Output Imp]-[Input Band Input Imp]-[Options]-[Modulator Firmware Option]

**Device Types:**

**IP** DVB-S2 IP Modem  
**DV** DaVid Technology Modem (combination of TS and IP into one carrier)

**Possible Options are:**

**DC24** 24 V DC power on L-band output  
**DC48** 48 V DC power on L-Band output  
**T11** one TS over IP input Interface  
**T12** two TS over IP input Interfaces  
**BI** BISS scrambling for Transport Stream Input  
**MT2** Support of 2 Multiple Transport Stream Inputs and Outputs

**Cannot be combined with:**

DC48  
 DC24  
 T12  
 T11  
 MT2-  
 BI

**Only available for:**

-  
 -  
 SK-DV  
 SK-DV  
 SK-DV  
 SK-DV

Modulator Firmware Option	Max Symbol Rate, Supported Modulation Types and other Features DVB-S2
- P2L	15 Msps, QPSK / 8PSK
- P2N	30 Msps, QPSK / 8PSK
- P2M	45 Msps, QPSK / 8PSK
- P2H	60 Msps, QPSK / 8PSK
- A2L	15 Msps, QPSK / 8PSK / 16APSK / 32APSK
- A2N	30 Msps, QPSK / 8PSK / 16APSK / 32APSK
- A2M	45 Msps, QPSK / 8PSK / 16APSK / 32APSK
- A2H	60 Msps, QPSK / 8PSK / 16APSK / 32APSK
- ...S	Support of Roll-Off-Filters down to 5%



Trade Mark of the DVB Digital Video Broadcasting Project

**Examples:**

**SK-IP-L50-L75-DC24-A2H** IP Modem with L-Band Output 50 Ω and L-Band Input 75 Ω, DC24 Volt  
**SK-IP-L50-L75-DC24-A2HS** IP Modem with L-Band Output 50 Ω and L-Band Input 75 Ω, DC24 Volt, Roll-Off-Filters down to 5 %  
**SK-IP-V50/L50-V75/L75-P2N** IP Modem with VHF-Band and L-Band Output, VHF-Band and L-Band Input  
**SK-DV-V75/L50-V75/L75-A2L** DaVid Technology Modem with VHF-Band and L-Band Output and Input