

Challenge Series Satellite High Speed DVB-S2 Modulator-Upconverter

Wide C-, X-, Ku-, K-Band



CCM, VCM, ACM Functionality

The satellite high speed DVB-S2 modulator / upconverter series combines WORK Microwave's 4th generation upconverters with a high-speed DVB-S2 modulator in one housing. This combination offers a cost and space saving solution. No extra modulator is required. The unit can be used in fixed satellite ground stations as well as in satellite news gathering (SNG) vehicles, Fly-Aways or any other mobile or portable applications.

New approach – better solution

For all high power TV-uplink which require low spurious emissions, two separate units were needed, a modulator plus a conventional upconverter. WORK Microwave's modulator / converter concept allows both units in one housing. This approach provides a very low spurious signal over the whole frequency band. In Ku-Band we cover the complete frequency range from 12.75-14.50 GHz with one unit only. The same is true for other bands. This is a significant advantage compared to the combination L-Band modulator / blockconverter.

MPEG Transport Stream Input-RF Output

The unit accepts an MPEG transport stream on an ASI or SPI input from a video encoder or MPEG multiplexer and provides a DVB-S or DVB-S2 modulated carrier in the C-Band, Ku-Band or K-Band, which can be directly connected to a high power amplifier.

Baseband Frame Data Input

For DVB-S2 VCM and ACM applications the modulator accepts on its input a baseband frame plus an additional header, which defines the modulation and FEC to be applied to each specific baseband frame. Also here the ASI or SPI input is used as interface. A hardware flow control signal can be used

for synchronization purposes between the modulator and the multiplexer or encapsulator.

High signal integrity

Low spurious emissions allow using the modulator-upconverters also in environments with demanding requirements, like high power video uplinks. Sophisticated temperature compensation guarantees gain stability over a very wide temperature range.

Flexibility, Backward Compatibility

Mode adaptation, FEC Encoding, and Modulation is compliant with the DVB-S2 Standard ETSI EN 302307. QPSK / 8PSK / 16APSK and 32APSK modulation is available. For backward compatibility also framing, scrambling, FEC encoding as well as QPSK / 8PSK / 16QAM modulation according to the DVB-S Standards ETSI EN 300421 and 301210 is supported. BPSK modulation is also possible. Carriers with symbol rates from very low rates (8 kbps) up to 60 Msps can be transmitted.

Operating and control – easy integration into your system

The converters can be operated via the push buttons on the front panel using self-explanatory display menus or via remote control (RS232, RS422/485, TCP/IP over Ethernet). Detailed monitoring of the system status and a summary alarm output (dual change over switch contacts) are provided. For remote control addressable, packet based commands are used.

Remote monitoring and control through SNMP and a Web browser interface is available.

Specials and OEM products

WORK Microwave is specialized to offer custom tailored products. We offer specials as follows:

- Dual- or Tri-Band versions
- Customized M&C interface and control syntax
- Extended storage or operating temperature range.
- Military versions for hostile environment (shock, vibration, humidity)
- Outdoor units

Key Features

- DVB Satellite modulator-upconverter for digital TV satellite uplinks and digital SNG applications
- DVB-S2 compliant (ETSI EN 302 307)
DVB-DSNG compliant (ETSI EN 301 210)
DVB-S compliant (ETSI EN 300 421)
- QPSK / 8PSK / 16 QAM modulation (DVB-S, DVB-DSNG)
- QPSK / 8PSK / 16APSK / 32 APSK modulation (DVB-S2)
- Normal and short FEC frames, Pilots on or off (DVB-S2)
- BISS-E encryption (option), supports multi program transport stream
- Physical layer framing (PL scrambling with codes 0 to 262141) according to DVB-S2 standard
- Roll-Off: 35%, 25%, 20%
- Roll-Off: 15%, 10%, 5% with Firmware Option ...S
- Adjustable digital slope equalizer
- Low spurious output
- Dual ASI (with auto-switchover) and SPI electrical interfaces
- ASI optical interface (option)
- Null packet insertion and deletion and with PCR correction
- Still picture playout (customized picture content can be loaded to the modulator unit, option)
- Symbol rates from 8 ksp/s to 60 Msps
- Data rate max approx. 213 Mbps with ASI Interface (depending on modulation type and FEC)
- Data rate max 267 Mbps with SPI Interface (depending on modulation type and FEC)
- Remote control through RS232, RS422/485 (2-wire or 4-wire) interfaces, TCP/IP over Ethernet, Web browser interface, SNMP (MIBs are provided).
- Summary alarm output (dual change over switch contacts)

- Transmit mute input
- 10 MHz Reference OCXO included
- Test output of modulated signal 1.4 GHz
- Operating temperature range -30°C to 60°C (-22°F to 140°F) (option)
- CE compliant
- **3 years warranty**

Customer Field selectable Firmware Option

Different maximum requirements are supported depending on the selected firmware option. The firmware option is password upgradeable in the field, which allows easy enhancement of the modulators if requirements change.

Summary of firmware options:

Firmware Option	Max Symbol Rate, Supported Modulation Types 1) DVB-S / DVB-DSNG 2) DVB-S2
- QL	20 Msps, BPSK / QPSK 1)
- QH	60 Msps, BPSK / QPSK 1)
- PL	20 Msps, BPSK / QPSK / 8PSK / 16QAM 1)
- PH	60 Msps, BPSK / QPSK / 8PSK / 16QAM 1)
- P2L	15 Msps, BPSK / QPSK 1) 15 Msps, QPSK / 8PSK 2)
- P2N	30 Msps, BPSK / QPSK 1) 30 Msps, QPSK / 8PSK 2)
- P2M	45 Msps, BPSK / QPSK 1) 45 Msps, QPSK / 8PSK 2)
- P2H	60 Msps, BPSK / QPSK 1) 60 Msps, QPSK / 8PSK 2)
- A2L	15 Msps, BPSK / QPSK / 8PSK / 16QAM 1) 15 Msps, QPSK / 8PSK / 16APSK / 32APSK 2)
- A2N	30 Msps, BPSK / QPSK / 8PSK / 16QAM 1) 30 Msps, QPSK / 8PSK / 16APSK / 32APSK 2)
- A2M	45 Msps, BPSK / QPSK / 8PSK / 16QAM 1) 45 Msps, QPSK / 8PSK / 16APSK / 32APSK 2)
- A2H	60 Msps, BPSK / QPSK / 8PSK / 16QAM 1) 60 Msps, QPSK / 8PSK / 16APSK / 32APSK 2)
- ...S	Support of Roll-Off-Filters down to 5%

Open questions, demo units

If you need more information about WORK Microwave's satellite modulators or if you would like to have demo a unit, please contact us via e-mail: info@drawcom.com.au or call us. We are glad to assist you.

Challenge Series

Satellite High Speed DVB-S2 Modulator-Upconverter

Indoor Unit

Wide C-, X-, Ku-, K-Band
S-Type (standard version), H-Type (extended temperature range)

Modulator-Upconverter Type:	HM2CU-C / SM2CU-C	HM2CU-X	HM2CU-Ku / SM2CU-Ku	HM2CU-K / SM2CU-K
Dualband (e.g. CKu, KuK) or Triband versions (e.g. CXKu, CKuK) are also available				
RF-Output Frequency:	C-Band 5.85 ... 6.65 GHz	X-Band 7.90 ... 8.40 GHz	Ku-Band 12.75 ... 14.5 GHz	K-Band 17.3 ... 18.4 GHz
Phase Noise:	10 Hz 100 Hz 1 kHz 10 kHz 100 kHz 1 MHz	-53 -73 -83 -87 -98 ¹⁾ -108 ¹⁾	-50 -70 -80 -85 -95 ¹⁾ -105 ¹⁾	-50 -70 -80 -84 -95 ¹⁾ -105 ¹⁾
max. values in dBc/ Hz ¹⁾ 0°C ... 50°C, outside this temperature range degraded by max 5 dB.				
Frequency Resolution:	10 Hz			
Conversion Scheme:	IQ-Modulator at 2450 MHz, single up-conversion			
RF-Output Characteristics:	Impedance: 50 Ω Return Loss: >20 dB >17 dB *) Output Power: -25 dBm ... 5 dBm, 0.1 dB steps -30 dBm ... 0 dBm, 0.1 dB steps *) Output Muting: >70 dB (by command or sense input or by alarm condition) RF-Connectors: SMA female *) valid for some dual band and all triband versions			
Test Output (Microwave Oscillator):	8.3 ... 9.1 GHz -7 ± 3 dBm -13 ± 3 dBm *) SMA female	10.35 ... 10.85 GHz -7 ± 3 dBm -13 ± 3 dBm *) SMA female	15.2 ... 16.95 GHz -7 ± 3 dBm -13 ± 3 dBm *) SMA female	14.85 ... 15.95 GHz -7 ± 3 dBm -13 ± 3 dBm *) SMA female
*) valid for some dualband and all triband versions				
Monitoring Output (on front panel):	Output Power: -20 dB of RF Output Impedance: 50 Ω Return Loss: >20 dB Connector: SMA female			
L-Band Test Output (Option LT)	Frequency: 990 MHz Level: -45 ± 3 dBm Connector: F female			
Spurious Outputs:	Signal related: <-70 dBc (Pout > 0 dBm) <-65 dBc (-20 dBm < Pout ≤ 0 dBm) <-60 dBc (Pout ≤ -20 dBm) -			
Frequency Stability:	±2 x 10 ⁻⁸ (-30°C ... 60°C, after warm up), aging: ±1 x 10 ⁻⁹ per day, ±1 x 10 ⁻⁷ per year			
Reference Input:	Frequency: 10 MHz or 5 MHz Level: -3 ... 10 dBm Modes: intern al, external, auto (senses reference input) Connector: BNC female			
Symbol Rate:	Max Range, depending on Firmware Option: 8 ksp/s ... 60 Msp/s Step size: 1 sp/s			
Clock Stability:	±2 x 10 ⁻⁸ (-30°C ... 60°C, after warm up), aging: ±1 x 10 ⁻⁹ per day, ±1 x 10 ⁻⁷ per year			
Data Rate:	3 kbps ... 267 Mbps (depending on firmware option, modulation, coding) (SPI interface) 3 kbps ... 213 Mbps (depending on firmware option, modulation, coding) (ASI interface) *) *) 3 kbps ... 170 Mbps (option BI, when BISS-1/E active)			
Transport Stream Adaption DVB-S2:	CRC-8 Encoder yes Merger/Slicer yes Baseband Header Insertion yes Stream Adaption yes Baseband Scrambling yes according ETSI EN 302307			
Transport Stream Adaption DVB-S / DVB-DSNG:	Transport Stream Adaption yes Randomization yes according ETSI EN 300421			
Modulation / Encoding DVB-S2:	Outer BCH Coding: FEC-Frames n _{ldpc} = 64800 (normal FEC Frame) or n _{ldpc} = 16200 (short FEC frame) Inner LDPC Coding, depending on Firmware Option: QPSK 1/4, 1/3, 2/5, 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 (only n _{ldpc} =64800) 8PSK 3/5, 2/3, 3/4, 5/6, 8/9, 9/10 (only n _{ldpc} =64800) 16APSK 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 (only n _{ldpc} =64800) 32APSK 3/4, 4/5, 5/6, 8/9, 9/10 (only n _{ldpc} =64800) Physical Layer Framing: yes Physical Layer Signaling: yes Pilots Insertion: on / off Physical Layer Scrambling: N=0 ... 262141 according ETSI EN 302307			

Specifications continued next page

Challenge Series

Satellite High Speed DVB-S2 Modulator-Upconverter

Indoor Unit

Wide C-, X-, Ku-, K-Band

Specifications continued:

Modulation / Encoding DVB-S / DVB-DSNG:	Outer Reed Solomon Coding: 188/204, T=8 Convolutional Interleaving: Depth I =12 Inner Coding depending on BPSK or QPSK 1/2, 2/3, 3/4, 5/6, 6/7, 7/8 (Convolutional K=7) Firmware Option: 8PSK 2/3, 5/6, 8/9 (Pragmatic Trellis) 16QAM 3/4, 7/8 (Pragmatic Trellis) according ETSI EN 300421, 301210
Transport Stream Input Interface:	DVB-SPI (DSUB25 female) and Dual DVB-ASI-electrical (2 x Connector BNC female, Impedance 75 Ω) auto switching (can be enabled) between input 1 and 2 in case of ASI signal interruption, ASI data missing DVB-ASI-optical (Connector ST female, Multimode, 1300 nm) (option, ask factory)
Baseband Frame Input:	Through DVB-ASI inputs or DVB-SPI input (can be used alternatively to Transport stream input, configurable) , Flow control signal available as LVDS Output signal on DVB-SPI connector or RS232 Signal on DVB-SPI connector (Option BBR)
Transport Stream Security (Option BI):	BISS-E Scrambler, compliant to EBU Tech 3292 rev. 2 Supports single or multi program transport streams in BISS Mode 0, 1 and E BISS Mode 0: no scrambling, MPEG transport stream is transferred untouched BISS Mode 1: MPEG transport stream is scrambled using 12-hexadecimal-character Clear Session Word BISS Mode E: MPEG transport stream is scrambled using a session word which is derived from a 16-hexadecimal-character Encrypted Session Word and 14-hexadecimal-character Injected Identifier Max. input rate for Clear Session Word and Encrypted Session Word: - 10 times per 5 minutes - 1 time per 10 seconds
Signal Spectrum Mask:	$\alpha = 0.35, 0.25, 0.20$ (according ETSI EN 300421, 301210, 302307) $\alpha = 0.15, 0.10, 0.05$ (with Firmware Option ...S, other values on request)
Transport Stream Frames Size:	188 or 204 bytes
Packet Stuffing:	TS Null packet insertion (DVB-S, DVB-DSNG, DVB-S2) or Dummy PLFRAME insertion (DVB-S2 only), when the data rate to transmit is higher than the data rate at the data input. Null packet deletion can be enabled to remove incoming null packets. PCR (program clock reference) correction (with Null packet insertion/deletion) for max 250 PID streams with PCRs included.
Still Picture Playout	As standard a color bar pattern is transmitted with main profile at main level (MPML) MPEG-2 encoding, 4:3 aspect ratio, 25 Hz frame rate, interlaced (suitable for PAL or SECAM). As option an alternative, customized still picture can be loaded (different content, different aspect ratio, different frame rate).
Compliant with Standards:	ETSI EN 300421, 301210, 302307 EN 50083-9 (ASI electrical, SPI Interface)
Monitoring:	Faults, stored faults with time stamps
Monitoring and Control Interface:	Protocol: SNMP
	Connection: UDP over Ethernet (10/100 Mbps, auto sensing), IPv4,connector RJ-45
	Protocol: HTTP (web browser interface)
	Connection: TCP/IP over Ethernet (10/100 Mbps, auto sensing), IPv4,connector RJ-45
Alarm Interface: Mute Input:	Protocol: Multipoint
	Connection: RS232 or RS422/RS485 (configurable), connector DSUB09 female or TCP/IP over Ethernet (10/100 Mbps, auto sensing), IPv4, connector RJ-45
Alarm Interface: Mute Input:	Alarm: two potential free contacts (DPDT), Mute Input: TTL logic input with internal pull up Connector DSUB09 female
Temperature Range:	HM2CU: -30°C ... 60°C operating (10 minutes warm up at -30°C) SM2CU: 0°C ... 50°C operating -30°C ... 80°C storage
User Interface:	SM2CU: LCD-Display 2 x 40 characters, 4 cursor keys, 4 function keys HM2CU: VFD-Display 2 x 40 characters, 4 cursor keys, 4 function keys (Option VFD for SM2CU)
Mains Power Input:	100 ... 240 V AC nominal, 90...264 V AC max, 50...60 Hz
Mains Power Consumption:	Typ: 45 VA / 30 W
Mains Power Input Connector:	IEC C14
Mains Fuse:	2 x 2 A time-lag fuse
Dimension and Weight:	483 x 44 x 505 mm ³ (WxHxD), 1 RU (19") approx. 10 kg

Specifications are subject to change

Challenge Series

Satellite High Speed DVB-S2 Modulator-Upconverter

Indoor Unit

Order Information:

SM2CU-[RF Band]-[Options] [Firmware Option]	Single Band modulator-upconverter
HM2CU-[RF Band]-[Options] [Firmware Option]	Single Band modulator-upconverter
HM2CUx-[RF Band(s)]-[Options]-[Firmware Option]	Multiband modulator-upconverter

x=2: Dualband modulator-upconverter, x=3: Triband modulator-upconverter

Possible Options are:	Cannot be combined with:	Requires:
VFD VFD display, standard with HCU-type converters	-	-
LT L-Band test output	-	-
FAN internal Fan	-	-
BBR Baseband Frame flow control as RS232 signal	-	-
BI BISS scrambling	-	-

Examples:

HM2CU-Ku-FAN-QH	Ku-band Modulator-Upconverter with fan
HM2CU-Ku-FAN-QHS	Ku-band Modulator-Upconverter with fan, Roll-Off-Filters down to 5 %
SM2CU2-KuK-P2H	Dualband Modulator-Upconverter KuK
SM2CU3-CKuK-FAN-A2H	Triband Modulator-Upconverter CKuK with fan



Trade Mark of the DVB Digital Video Broadcasting Project